

Model: NXG3251D3KC(336 /6×4 /14.9m³)Tipper 自卸车**Dimensions(mm):尺寸(毫米)**

Overall size (length×width×height) 外形尺寸(长×宽×高)	8115×2495×3380
Cargobody size (length×width×height) 货厢尺寸(长×宽×高)	5400×2300×1200
Wheelbase 轴距	3650+1350
Wheel tread (Front/Rear) 轮距(前/后)	2057/1848
Min. ground clearance 最小离地距离	290

Weight(kg): 重量(公斤)

Kerb mass 整备质量	12400
Gross vehicle weight 总质量	24995

Performance:性能参数

Max. travel speed 最高车速	90km/h
Min. turning diameter 最小转弯直径	16m
Max. gradeability 爬坡度(%)	30%
Approach angle 接近角	26°
Departure angle 离去角	20°

Engine:发动机

WP10.336N,water-cooling,turbocharging and intercooling, Euro III emission standard, direct injection diesel
水冷,涡轮增压,中冷,欧III排放标准,直喷式柴油机

Rated output at 1,900rpm 额定功率	336HP(247kw)
Max. torque at 1200r/pm 最大扭矩	1500N.m
Rated Fuel consumption 油耗比	196g/(KW.h)

Driver's Cab:驾驶室

tiltable cab , with air-conditioner & ventilation, adjustable
R driver's seat ,single sleeper
可翻转驾驶室,带空调和通风系统,可调式司机座椅,单卧

Transmission:变速箱

Type (型号) : RT-11509C
9 forward/1 reverse 前进9档/后退1档

Steering:转向装置

hydraulic steering with power assistance 液压助力转向

**Front axle:前桥**

7.5T Elliot type, I beam section 端拳式, 锻钢工字梁结构

Rear axle:后桥

26T

Ratio 速比: 4.8

Clutch:离合器

Single-plate dry coil-spring clutch, diameter 430, hydraulically operating with air assistance 单片干式螺旋形弹簧, 直径430, 空气助力的液压操作

Brakes:刹车

Service brake 行车制动:dual circuit compressed air brake 双回路空气制动

Parking brake 停车制动:spring energy operating on rear wheels 后轮弹簧气室制动

Auxiliary brake 辅助刹车:engine exhaust brake 发动机排气制动

Wheels rim& Tyres:轮胎

Rims 钢圈 8.50V-20

Tyres 轮胎 12.00R-20

Electric System:电力系统

negative grounded 负极搭铁

Operating voltage 操作电压 24V

Alternator 交流发电机 70A/28V

Fuel tank: 油箱

Capacity 容积 240 L

All specifications are subject to modifications without notice.
本公司保留随技术改进而修改参数的权利